BUNLINFMEMP

CLASSIFICATION

CONFIDENTIAL

RE2ORT

50X1-HUM

CENTRAL INTELLIGENCE AGENCY
INFORMATION FROM

FOREIGN DOCUMENTS OR RADIO BROADCASTS

CD NO.

COUNTRY

Yugoslavia

DATE OF

INFORMATION 1950

SUBJECT

Transportation - Air, glider

HOW

PUBLISHED Monthly periodical

DATE DIST. 29 May 1951

WHERE

PUBLISHED

Belgrade

NO. OF PAGES 2

DATE

PUBLISHED

Nov 1950

SUPPLEMENT TO

LANGUAGE

Serbo-Croatian

REPORT NO.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF ESPIONAGE ACT BU W. S. C., 21 AND 22, 25 AMERGED. ITS TRANSMISSION OF THE REVELATION OF ITS CONTENTS IN ANY BARNER TO AN UNAUTHORIZED PERSON IS PRO-NIBITED BY LAW. REPRODUCTION OF THIS FORM IS PROVIDILLO.

THIS IS UNEVALUATED INFORMATION

SOURCE

Narodna Krila.

NEW YUGOSLAV AMPHIBIOUS GLIDER

In February 1950, the nucleus of a construction bureau was formed in Zagreb, to worklout the blueprints for the prototype of the "Split H-49" amphibious glider and verify the figures of Fran Hranueli, a Zagreb technical student who conceived the basic plan. Other members of the bureau are Antun Cvetkovic, Ranko Efenberger, Borislav Vajic, Kreso Parapatic, Milojko Vucelic, and Emil Fresl.

Designs for the wooden parts and the main fittings and controls of the "Split" are completed, and details of the hull and brakes are being finished. A frame for the fuselage and ribs for the wings are being built in the workshop set up by the bureau members. It is estimated that the "Split" will be completed in May 1951.

The "Split" is the second Yugoslav single-place amphibious glider, is entirely constructed of wood, and should have better character; ities than the "Jadran." The specifications are as follows: wing span, 18.5 meters; ratio of fuselage, length to width; 1:19.5; amount of fuselage taper, 1:2.8; profile NACA 2415 at the root, N 71 at wing tipe; and length, 7.68 meters. The fuselage is a two-step hull, and two floats of 1.05 meters height fold mechanically into the wing.

The optimum soaring angle is 1:28.2 at a speed of 73.5 kilometers per hour, and the speed of descent 0.75 meters per second.

The minimum speed of descent is 0.65 meters per second, at 60.3 kilometers per hour; 1.25 meters per second, at 100 kilometers per hour, and 2.15 meters per second, at 120 kilometers per hour. Diving speed with brakes is reduced to 200 kilometers per hour.

Upon completion the "Split" will be tested in the Adriatic, possibly with the aid of the unfinished "TPZ," plane which has a 130-horsepower engine. Instead of landing gear, pontoons of the Yugoslav "Aero 2H" seaplane would be installed to provide a tow plane for the amphibious glider.

Also being constructed is a light, single-place vocaen plane, with a 30-boungouse [60] cagine. Whe intention also is to train eagine pilots and reform no-collect "6" glader

-1-

CONFIDENTIAL

CLASSIFICATION								COMPIDENTIAL						- '-								
	STATE	X	HAVY	X	NSRB		DISTRIBUTION						. 1 '		L			Ш	p155		انا	
	ARMY	X	AIR	X	FB1											<u> </u>			ــنا	<u> </u>	Ш	
	Paramon Acres	N. T.	Andrewski	tana e arres	ilian illigione di seriesi di ser		34		ا رقيع ان	Adjusted Contracts	and the second	e je se s	gra.	ا اخراف معرود	ر ر دخانده	ا اع آزارلگلیک	ne de parece ne despuise	timent ce	de la constanción de	*****	Valat	٠,

Also being constructed is a light, single-place wooden plane, with a 30-horsepower "KDF" engine. The intention also is to train engine pilots and retrain so-called "C" glider pilots in the aeroclubs. The project may be completed by the end of 1950 and will be finished by spring 1951 at the latest.

50X1-HUM

Sanitized Copy Approved for Release 2011/10/19: CIA-RDP80-00809A000600390453-6

- E K D -

- 2 -

CONFIDENTIAL

CONFIDENTIAL